

Calibration of torque wrenches:

Offer



1 General

ESTL calibrates torque wrenches with a nominal range of 30 to 1000 Nm. The calibration is done with an autonomous calibration device in accordance with the principles of ISO 6789. The calibration can be done clockwise, counter-clockwise or in both directions.

2 Practical conditions

- The torque wrenches must be marked before they are delivered to ESTL.
- A calibration is officially requested via the website www.estl.be, or via a signed application form by mail sent to kalibratie@estl.be. The data in the application form are absolutely necessary to be able to carry out the calibration. In case of incomplete data, extra administration and communication costs can be charged.
- Torque wrenches are sent without the corresponding sockets.
- The torque wrenches are sent to ESTL in a reusable packaging that will also be used for the return shipment. Alternatively, they are delivered and collected in the ESTL lab in Deerlijk.
- The shipping costs are paid back and forth by the applicant.
- Calibration certificates are sent to the client by mail in pdf format.

3 Price

Calibration	1 direction	2 directions
Price	43,5 €	58,5 €

- Optional application of a calibration label: free of charge.



- For services of less than € 125 (excluding VAT), an administration fee of 8 € is charged.
- Costs for shipping, return shipping, return packaging if required and VAT are at the expense of the client.

4 Delivery time

- The standard lead time is 10 to 15 days
- ESTL always reserves the right to a longer delivery period, but only invokes this in exceptional situations.

5 General conditions

- Any damage caused by ESTL when carrying out calibrations, of whatever nature, is compensated but limited to the anticipated cost of calibrating the damaged torque wrench. The causal burden of proof lies with the client.
- ESTL reserves the right not to calibrate a received torque wrench without further motivation.

Request Form



1. Company details

Company			
Service			
Street+ Number			
City		Postal code	
Country			
Person Responsible			
Function		Phone	
E-mail			
Order number		VAT number	

2. Object data

Instrument type (eg. Torque wrench)	
Brand (eg. Hazet)	
Type / model (eg. 5122-1CT)	
Internal company code (eg. MMSLTL_01)	
Serial number (eg. 123456)	
Maximum capacity (eg. 200)	
Minimum capacity (eg. 40)	
Capacity : unit (eg. Nm)	
Signal output max. (eg. 20), often: does not apply	
Signal input min. (eg. 4), often: does not apply	
Signal : unit: (eg. mA), often: does not apply	
Calibration direction (eg. clockwise and/or counter-clockwise)	
Type according to ISO 6789 (often: II) view F INFO MCT T	
Class according to ISO 6789 (often: A) view F INFO MCT T	
Applying calibration label:	yes/ no
Desired calibration term (max. 1 year)	

3. Extra

-After calibration, the calibration certificate is mailed to the client. This email will ask you to request a return shipment. ESTL uses the shipping packaging for the return shipment.

For approval,

The contractor